


DOP: Spaandex EN 312 P5					
1. Product-type:	Particleboard acc. to EN 312 P5				
2. Product-name	Spaandex EN 312 P5				
3. Intended use	Load-bearing board for use in humid conditions in permanently heated surroundings.				
4. Manufacturer	Kronospan ApS Novopan Træindustri Fabriksvej 2, Pindstrup DK-8550 Ryomgård				
5. Authorised Representative	Not relevant				
6. System of AVCP.	AVCP 2+				
7. Notified Body	Dancert A/S Gregersensvej 4 DK-2630 Taastrup				
8. Declared performance *: EN 321	Thickness	>10-13 mm	>13-20 mm	>20-25mm	EN 13986:2004 EN 312:2010
	Bending	≥ 18 N/mm ²	≥ 16 N/mm ²	≥ 14 N/mm ²	
	Mean Stiffness (MOE)	≥ 2550 N/mm ²	≥ 2400 N/mm ²	≥ 2150 N/mm ²	
	Internal bond	≥ 0,45 N/mm ²	≥ 0,45 N/mm ²	≥ 0,40 N/mm ²	
	Swelling 24 timer	≤ 11 %	≤ 10 %	≤ 10 %	
	Internal bond after cyclic test*	≥ 0,25 N/mm ²	≥ 0,22 N/mm ²	≥ 0,20 N/mm ²	
	Formaldehyde	≤ 8 mg/100g v. 6,5% fugt	≤ 8 mg/100g v. 6,5% fugt	≤ 8 mg/100g v. 6,5% fugt	
	Brandklasse	Ds2-d0	Ds2-d0	Ds2-d0	

The performance of the product identified is in conformity with the declared performances.



 Henrik Skovbo, laboratorie- og kvalitetschef
 KRONOSPAN ApS
 PINDSTRUP
 8550 Ryomgård

Pindstrup d. 09-05-2022